



### Rolling Shutter Installation Instruction Sheet

#### Tools Needed

- Cordless driver
- Rubber mallet
- #1 Square head driver
- Phillips driver
- Level
- Measuring Tape
- Pencil

#### Hardware provided by TRS per unit

- Housing (1)
- Rails (2)
- Remote/Switch
- Green Motor Limit Setting Tool (1)
- U-channel (if applicable)

#### Step 1

- A. Open boxes when received to verify freight damage free product and all parts are included.

#### Step 3

- A. Place products near where the installation will be taking place.

- B. Measure unit and rails.
- C. Strip protection film.

### Step 3

- A. Measure opening to determine centering of the unit.
- B. Using a pencil, tick mark rail height and overall width. Equal reveal is key.
- C. Rail height, where applicable, should be 1.5" (depending on the application) above the opening and 1.5 below, so bottom slat is not visible when all the way up or down.

### Step 4

- A. Mount rails.
- B. Place rails on previously marked dimension from step 3. B.
- C. Install bottom screw and work your way up.

Exception: If there is not enough clearance to drop housing box onto rails, all will have to be installed together as one.

- D. Over tightened screws can cause issues like tweaking or bending of rails. Rails should not conform to the wall.
- E. Check levelness.
- F. Check OAW/ID.

Note: If shutter had a u-channel, install center screw for support and to prevent sagging.

### Step 5

- A. Hang housing onto rails.
- B. Confirm levelness (Make any adjustments if necessary).
- C. Double check OAW/ID straight across to each mounting point.
- D. Tighten down all rail screws (Do not over tighten).

### Step 6

- A. Power up unit and program remote within your 10 second window. Refer to programming instructions. [Click on link to your designated motor for programming instructions.](#)
- B. Set top and bottom limits. Refer to limit setting instructions. [Click on link for instructions.](#)
- C. Run rolling shutter down to install back screws in upper corners.

- D. While shutter is down, install back screws on upper or lower corners.

#### Step 7

- A. Run unit up and down to confirm limits and smooth operation of your shutter.
- B. Install hood.
- C. Wipe down hardware.